





MADE IN FRANCE





A TECHNOLOGICAL BREAKTHROUGH!

Deus marks a technological breakthrough and is a real innovation in metal detector design. Its patented design is based on three elements: A Coil, a Remote Control and a set of Audio Headphones, which are unique in that they Headphones, which are unique in that they communicate with each other via a digital radio link. Through the incorporation of cutting-edge technologies, DEUS delivers power, speed and precision, all in a lightweight and compact design. The search coil contains the essential components for processing the signals, which no longer need to be conveyed via a wire link. The signal is digitized and analysed directly at the source by an ultra-miniature digital circuit, this greatly improves the quality of signal acquisition.

DEEPER & FASTER!

- · Many advanced feactures.
- · Large frequency choices and settings.

LIGHTER, MORE COMPACT!

- · Utra light detector: 900g full (800g without remote).
- Pocket size remote control.
- Double D coil, light and waterproof.
 Wireless headphones, with their own operational
- Lithium Battery

		HF GOLD PRO	COIL SPECTING		X35	
THE TO SERVICE OF THE PROPERTY	COIL5	HF COIL	Ch.	*	*	(D)
	SUGGESTED USES	Gold prospecting - Very small targets Mineralised ground		General use - Big and small targets All terrain		
	NAME / SIZES	ELLIPTICAL HF COIL 24x13cm - 10" x 5"	22 HF COIL 22 cm - 9"	22 - X35 COIL 22 cm - 9"	28 - X35 COIL 28 cm - 11''	34x28 - X35 COIL 34x28 cm - 13''x11''
	FREQUENCY	21 FREQUENCIES 13 kHz to 81 kHz	21 FREQUENCIES 13 kHz to 59 kHz	35 FREQUENCIES 3.7 kHz to 27.7 kHz	35 FREQUENCIES 3.7 kHz to 27.7 kHz	35 FREQUENCIES 3.7 kHz to 27.7 kHz
	LITHIUM BATTERY	830 mAH	830 mAH	630 mAH	630 mAH	630 mAH
	BATTERY LIFE	± 24 H	± 24 H	± 15 H	± 15 H	± 15 H
	TX BOOST / TX NORMAL	ND	NΠ	YE5 frequencies 3.7 to 4.4 kHz	YE5 frequencies 3.7 to 4.4 kHz	YE5 frequencies 3.7 to 4.4 kHz
	WATERPROOF 6M	YE5	YE5	YE5	YE5	YE5
®	WEIGHT	360 g	380 g	370 g	470 g	590 g
XP METAL DETECTORS						* Sold as a standard package

Specifications can be changed without notification



• Suggested uses		Gold prospecting Mineralised ground								
CONFIGURATIONS										
• Coil	22 cm - 9" 28 cm - 11"	22 cm - 9" 28 cm - 11"	22 cm - 9" 28 cm - 11"	22 cm - 9" 28 cm - 11"	22 cm - 9'' 28 cm - 11''	24x13 cm 22 cm				
• Remote Control	Y	Y	Y			<u> </u>				
• Wireless headphones	W54	W55		W54	W55	W54				
FUNCTIONS										
• Discrimination	V	~	✓	V	V	V				
• Sensitivity					¥	Y				
• Ground balance / Tracking / Pumping mode	V	~	✓	V	V	Y				
• 1 to 5 Tones + Pitch + Full Tones					¥	\vee				
• Multi-tones , expert mode, fully adjustable	V	~	✓			V				
• Frequency		21 FREQUENCIES								
• Freq. shift		13 to 81 kHz 13 to 59 kHz								
• 10 factory programs + 8 user					¥	\vee				
• Reactivity	Y	Y	V	Y	Y	V				
• Pinpoint / 4 non-motion modes						Y				
· Iron level	Y	Y	Y	V	Y	V				
• Notch / Multi-Notch						Y				
• Notch ground	Y	Y	V			Y				
• Tx Power					¥	\vee				
• Silencer	V	V	Y			V				
• Audio Response	¥	¥	¥	¥	Y	¥				
• Beach programs	V	V	V	V	V	V				
• ID Norm	ON / OFF	ON / OFF	ON / OFF	ΠN	ΩN	OFF				
• USB / Update	<u> </u>	VIA REMOTE CONTROL								
· Control DEUS with the wireless headphone					¥	Y				
• Lithium Battery	RC/W54: 27H - Cail: 15 H	RC/WS5: 27H - Coil: 15 H	RC: 27H - Coil: 15 H	W54: 27H - Coil: 15 H	WS5: 27H - Coil: 15 H	RC/W54: 27H - Cail: 24H				





